



# InDashNet® UN8000 Android Head Unit Specification

---

## Highlight

The most powerful hardware: 8-core/2GB DDR/32GB EMMC  
15 seconds cold booting time, smooth running for large Apps  
High sensitive global radio  
Built-in GPS, Wifi, Bluetooth hands-free(ParrotBT optional)  
Immediate reverse camera, auto-dim brightness  
both built-in AMP & RCA plus subwoofer  
Support 4+ Cameras for reverse, aux, side view, front view  
1080P HD video playback & recording  
Google Play store & Google Apps

---

## Computing platform

CPU: 8-core ARM Cortex-A7  
RAM: 2GB DDR3  
Flash storage: 32GB eMMC 5.0  
Android 5.1.1 Lollipop(continuous updateing)

---

## Display

Wide screen with multi-touch

7", 1024x600  
(6.2-10.1" display available on specific models)

---

**Wireless connectivity**

Wi-Fi 802.11 b/g/n  
Bluetooth: standard Car-kit features (hands-free, phone book etc.)  
Wireless data: support select models of USB 3G/4G wireless modems (WCDMA/EVDO/LTE), availability varies by region  
Support select TPMS (tire pressure management system) sensors

---

**USB spec**

USB 2.0 HighSpeed  
Power supply: 500mA/5V front port, shared 3A/5V back ports (no ID)

---

**Wired/plug-in devices**

SD/SDHC card, FAT16/FAT32, 32GB max  
USB mass storage: thumb drive, portable disk  
HID devices: USB keyboard and mouse  
USB hub for port expansion  
USB camera for video recording

---

**Multimedia playback**

Video codec: H263, H264, H265, VP6, VP8, VP9, MPEG 1/2/4-XVID, DivX 3/4/5, WMV 7/8, VC-1  
Audio codec: MP3, AAC, OGG, WMA, APE, FLAC  
File formats: MKV, MP4/M4V, WebM, FLV, WMV, AVI, MOV, VOB, TS/TP  
Max video resolution 1920x1080 @60fps (may be limited by codec/container spec or bit rate)

---

**Video subsystem**

Video source: front view, side view, rearview

Video output: On-unit display, headrest display

Recording format: H264/AAC, max 1920x1080@60fps (USB camera)

---

**Radio**

AM: 510K~1720KHz, 9K or 10K stepping

FM: FM 65~108Mhz, 50KHz stepping, RDS supported

Both bands have global coverage; settings follow regional regulations

---

**Audio input/output**

AUX input

Standard 4-way output: FL,FR,RL,RR

Poweramp output 45Wx4

4-Channel RCA, Subwoofer

---

**Physical**

Dimensions: 2 DIN, 178 x 100 x 175mm (7.0 x 4.0 x 6.9in)

Install weight: 2.0Kg (4.4lb)

---

**Power & environment**

Voltage: 9.5~15V DC

Consumption: 15A max

Temperature: -20~70 °C (-4~158 °F), non-condensing

---